

Price List-Quotation

Model No.	Description	Units	FOB Qingdao Price
XQ5032B	Vertical Milling Machine 3-axis auto-feed by servo motor	1	

Standard Accessories

Name	Specification Model	Qty
Draw bar	M16 X430	1 set
Inner hexagon spanner	5	1
Double-ended wrench	17*19	1
Double-ended wrench	22*24	1
Lifting crank		1
Nut	M16	2

Optional Accessories

NO.	Name	Price(USD)
1	CE Schneider electric	
2	Aluminum hangarm	
3	3-axis DRO	
4	Spindle cover	
5	Worktable cover	
6	LED work lamp	
7	Automatic central oil lubrication	

Main Features

- 1.Head stock swivel $\pm 30^{\circ}$
- 2.Spindle is driven by gears, 12 steps speed, the machine is applied to heavy cut
- 3.Driven by servo motor.
- 4.Table automatic feed on X Y Z
- 5Automatic rapid feed X Y Z

Specification

Specification	Unit	XQ5032	XQ5032A	XQ5032B	XQ5032C
Table size	mm	1270X320	1370X320	1270*320	1370*320
Table Travel (X/Y/Z)	mm	720/300/400	820/300/400	900/380/400	1000/380/400
Distance from spindle nose to work surface	mm	35-435			
Spindle hole taper	---	7:24 ISO40			
Rapid speed of table (X/Y/Z)	mm/min	1335/1335/1000			
Table feed (X/Y/Z)	mm/min	XY: 30-830 Z: 23-625			
T-slots (NO./Width/Pitch)	mm	3/14/80			
Spindle speed range	r/min	12 级 steps 35-1500			
Stroke of spindle quill	mm	70			
Distance between spindle axis and column guideway	mm	285			
Swivel angle of Vertical milling head	---	$\pm 30^{\circ}$			
Main motor power	kw	3			
Torque of X/Y/Z axis AC servo motor	N.m	10			
Overall size	mm	1720X1680X1810	1820X1680X1810	1720X1680X1810	1820X1680X1810
Net weight	kg	1550	1600	1600	1650



